

LIFTING TECHNOLOGY PIT JACK

**MPJ 16.5/1200 2S FA
STOCK**
VP 454278



MPJ 16.5/1200 2S FA STOCK VP 454278

The axle and transmission jack lifts up to 16.5 t. The floor-running axle and transmission jack, with double telescopic cylinders (max. stroke 1200 mm), is freely moveable; at 1000 kg it automatically lowers. Load-free, a compressed air speed control function ensures fast movement of the two telescopic segments as well as fast retraction of the piston rods. The equipment also includes an air motor with foot pedal control for lifting the piston rod under load.

PRODUCT DETAILS/ACCESSORIES

2-stage telescopic, free-moving, floor-running

Description:

Automatic axle and transmission jack with pneumatic motor and fast control in slim design specifically for dismantling assemblies and lifting vehicles up to 16.5 t

Control:

- Unique synchronised telescopic lifting cylinder for quick load lifting with fast control
- Efficient fast control for UP and DOWN movement integrated as standard
- Precision, user-friendly foot control using compact and robust operating unit for quick lift and load lift
- Delicate and precision lowering of the pit jack with tried (>>) tested system with integrated dead man's control
- Telescopic stages protected against corrosion thanks to the Venturi effect (separation of hydraulic oil and airflow)
- Integrated cover to protect against unintentional operation

Design:

- Freely movable floor-runnable pit jack for flexible use at various work locations, e.g. workshops or work pit

- Floor-running carriage with four guide rollers, two of which are fitted with brakes to prevent rolling away (without load)
- Spring-based roll guard: jack automatically lowers itself to floor once a load capacity of about 1000 kg is reached, securing itself in the process
- Integrated inspection window for checking oil quality and quantity of the pit jack
- Optimised removal of the dismantled units thanks to low construction height of the jack due to ideal arrangement of the lifting unit in the carriage
- With its non-slip coating the carriage can be used as a secure working platform for ergonomic reasons
- Corrosion-resistant piston rods thanks to self-lubrication
- High-quality powder-coating protects against corrosive liquids and elevates quality look and feel on a lasting basis

Scope of delivery:

- Pit jack with hydro-pneumatic automatic control system
- Carriage with four guide rollers
- Standard support lugs 120 x 120 mm
- Operating instructions
- EC conformity certificate
- Colour: Jack base frame RAL 7040
 - Attachments and carriage RAL 7016

TECHNICAL DATA

Load capacity (CE)	16,500 kg
Fast stroke power	400 kg
Stroke distance	1200 mm
Lifting levels	2
Min. load pick-up height	867 mm
Max. lifting height	2067 mm
Carriage (L x W)	1010 x 760 mm
Rollers	80 mm (polyamide)
Support diameter inside/outside	45/80 mm

LIFTING TECHNOLOGY PIT JACK

MPJ 16.5/1200 2S FA
STOCK
VP 454278



TECHNICAL DATA

Piston roddiameter	80/115 mm
Oil quantity/quality	15.3 l / HLP-D 10
Drive	350 l/min. 8-10 bar
Operating pressure	235 bar
Weight	300 kg

ACCESSORIES

VZ 975920	Jack-mounted compressed air maintenance unit	VZ 975287	Lifting Pad w. Rubber Surface, 11 t Load Capacity MODEL: RPG 10
VZ 975744	Pneumatic manual control cylinder with magnetic bracket	VZ 975369	Lifting Pad with Rubber Surface, 2 - 4.5 t Load Capacity MODEL: RP 125
VZ 975919	Precision-control foot lever	VZ 975289	Plug-In Extender, L = 100 mm, MODEL: ZS 100/45
VZ 975670	Self-locking axle lifting beam with 14.5 t support system MODEL: SAT 14.5-760	VZ 975290	Plug-In Extender, L = 150 mm, MODEL: ZS 150/45
VZ 975813	Self-locking axle lifting beam with 14.5 t support system MODEL: SAT 14.5-820	VZ 975410	Plug-In Extender, L = 200 mm MODEL: ZS 200/45
VZ 975622	Self-locking axle lifting beam with 14.5 t support system MODEL: SAT 14.5-910 STOCK	VZ 971221	Support Plate Extension 100 mm galvanized (2 pcs.) Diameter of supports 35 mm
VZ 975741	Self-locking axle lifting beam with 14.5 t support system MODEL: SAT 14.5-910L	VZ 975330	Support Tube L = 400 mm, Load Capacity: 20 t (Pin Diam. 45 mm)
VZ 975743	SAT Rollers Retrofit Kit, Spring Mounted, with Plastic Rollers	VZ 975331	Support Tube L = 600 mm, Load Capacity: 20 t (Pin Diameter 45 mm)
VZ 975814	SAT Wheel Deflector Plates (2 pcs)	VZ 975571	Support Tube L = 800 mm, Load Capacity: 15 t (Pin Diameter 45 mm)
VZ 975820	Spacer Block for Support Systems SAT (65 x 110 x 320 mm)	VZ 975414	Spacer Block for Support Systems TAB (100 x 140 x 450 mm)
VZ 975903	Axle lifting beam up to 15 t Adjustment range max. 1010 mm MODEL: AT 15	VZ 975732	Gearbox Plate, Load Cpc. 1.0t Model: GP 1000
VZ 975688	Axle Traverse Length Variation	VP 975915	Gearbox Mounting Tool with swivelling flat supports MODEL: GMT 800
VZ 975906	Axle traverse Long for busses, com. vehicles, 16.5t load cap. MODEL: AT 16.5 L1500	VZ 975916	Swivel supports for GMT 800 w. locking function
VZ 975696	Axle Crossbar Load Capacity 3.5 t Model: ATV 3.5	VZ 975917	Angle clamp supports for GMT 800 with rubber pad
VZ 975925	Support bridge for axle traverses up to 14.5 t load capac. MODEL: TAB 15	VZ 975918	Semicircular flex supports for GMT 800 with rubber pads
VZ 975326	Support Bridge AB w/o Centre Cut-Out up to 14.5 t Load Cpc. MODEL: AB 15	VZ 975611	Pit crossing continuously adjustable for pits w/o wheel guides
VZ 975686	Support System Version D/F	VZ 975612	Pit crossing continuously adjustable for pits with wheel guides
VZ 975687	Support System Version E	VZ 975613	Railings for pit crossing continuously adjustable
VZ 975280	Narrow Lifting Pad, 20 t Load Capacity, galvanized, up to 100 mm (Pin Diameter 45 mm)	SUPPLEMENTARY CHARGES	
VZ 975285	Large Lifting Pad, galvanized, Load Capacity 20 t MODEL: GP 175/20	VT 998207	Internal transport -SOUTH Pit, Axle, Gearbox jack Support system (per package)
VZ 975283	Large Lifting Pad, galvanized, Load Capacity 16.5 t MODEL: GP 220	VT 998208	Internal transport -NORTH Pit, Axle, Gearbox jack Support system (per package)
VZ 975569	Pads with mushroom support N with pin diameter 45 mm MODEL: PS-N	VM 996148	Montagekosten Grubenheber
VZ 975409	Wooden Lifting Pad, 6 - 16 t Load Capacity, Prismatic Design, MODEL: HP 06-16	VV 997600	Packaging Floor-running jack not stackable -EUROPE/OVERSEAS-
		VV 997601	Packaging Lifting beams, gearbox plates, stackable -EUROPE/OVERSEAS-