

# LIFTING TECHNOLOGY

## MOBILE COLUMN LIFT

**RGE TS**  
VP 451133



### RGE TS

#### VP 451133

The mobile wheel engaging COLUMNLIFT RGE TS, with two crosspieces with adapter kit, is specifically for the lifting of tractors (equipped with corresponding C-rail), and lifts up to 7.5 t per column. Streamline column design offers a good overview when manoeuvring. The low-maintenance, electro-mechanical drive system ensures extremely smooth running while the excellent mechanical rigidity of the columns guarantees safety and the ability to function in any condition. A high-quality worm gear motor enables precision height positioning without overrun. Column communication is via connecting cable, the power supply via mains power.

#### PRODUCT DETAILS/ACCESSORIES

- Very smooth running due to electro-mechanical drive system
- High efficiency thanks to smooth-running, low-maintenance ball screw
- 5-year warranty for entire spindle drive
- Excellent lifting column mechanical rigidity guarantees safety and function under any conditions
- Specially for holding tractors with two crosspieces with adapter kit (can only be used for tractors with corresponding C-rail)
- Precision-height positioning without overrun thanks to high-quality worm gear motor
- Lifting carriages with fixed holder
- Overhead drive unit creates even more space in the work area
- Workshop-robust and splash-proof control unit
- Wear-free and easy-to-use membrane keypad
- Flexible column positioning thanks to excess-length connection cables, guaranteeing suitability across all vehicle categories
- User convenience with panel operator controls on each individual column
- High level of flexibility in use due to different operating modes
- Group and individual column operating modes enable quick and easy replacement of wheel and axle suspensions
- Microprocessor control and CAN bus-supported monitoring of movement synchronisation and all safety functions
- Utmost safety thanks to mechanically independent locking device
- Simple emergency lowering for power failure included as standard
- System can easily be expanded with up to six columns
- Streamline COLUMNLIFT design aids manoeuvrability specifically in workstations with restricted space
- High-quality powder coating:
  - Window Grey, RAL 7040 (Columns)
  - Anthracite, Grey RAL 7016 (Lifting carriages)

#### Scope of delivery:

- 2 individual mobile columns
- 1 connecting cable (10m) with plug and socket
- 1 mechanical dolly, repositionable
- 2 crosspieces with adapter kit

#### TECHNICAL DATA

Load capacity CE per column	7500 kg
Drive power per column	1.5 kW
Weight per column	452 kg
Lifting distance	1750 mm
Raising/lowering time	113 s
Supply voltage	3/N/PE 400 V 50 Hz
Protection rating	IP 54

#### ACCESSORIES

- VZ 971260 Single RGE Post (MAHA), 7500 kg lifting capacity incl. connection cable & plug
- VZ 971182 Remote Control TCNA 10-2 for RGE Up/Down with emergency stop switch

- VZ 971179 Removable Mechanical Dolly, MODEL: MFR-2
- VZ 971181 Hydraulic Pallet-Type Fixed Dolly, screwed onto post MODEL: MFP

# LIFTING TECHNOLOGY

## MOBILE COLUMN LIFT

RGE TS  
VP 451133



VZ 971164 Support Stand AB 6-07, lifting capacity 7500 kg,  
adjustment range 470 - 795 mm (each)

VZ 971165 Support Stand AB 6-12, lifting capacity 7500 kg,  
adjustment range 875 - 1395 mm, mobile

VZ 971166 Support Stand AB 6-20, lifting capacity 7500 kg,  
adjustment range 1200-1965 mm, mobile

VZ 971168 Screw Adjustment SP 75 for AB 6-07/12/20  
Support Stands

VZ 990456 Linking cable 15 m -Extra charge per cable

VZ 990457 Linking cable 20 m -Extra charge per cable

#### SUPPLEMENTARY CHARGES

VT 998032 Transportkosten 2 Einzelsäulen inkl. Verpackung

VT 995698 Transportkosten 4 Einzelsäulen inkl. Verpackung

VT 995699 Transportkosten 6 Einzelsäulen inkl. Verpackung

VM 996077 Installation costs for mobile column lifts